


Neotech Marken SARL 74 Rue Jean Monnet - Z.A La Sensive 44450 LA CHAPELLE BASSE MER - FRANCE Tel : + 33 (0)2 40 31 24 73 yann.chauvire@neotech-marken.com www.neotech-marken.com

## NK-30

Service Workshop Hose Crimper max. 1.1/4" 4-SP



Option : QCT-NLS



Option : PDR-1



The use of this machine is ideally recommended for service hose assembly up to 1 1/4''-4-Wire spiral.

The capacity of this machine covers the most widely used hoses on the market and thanks to its large opening you can pass 2 x 90 deg. elbows with BSP nut up to 1 1/4".

We recommend the use of this machine for an intermittent use of approximately 50 to 100 hose assemblies per day



Option : WP-12PDR

Technical Description NK-30	
Maximum capacity :	2-SN : 1 ½" (DN32; -20)
For an intermittent use in high pressure hose	4-SP : 1 1/4'' (DN32, -20)
assembling	6-SP or Interlock :1" (DN25, -16)
Motor	2.2 kW - 400V 3-PH 50hz (NK30P.1)
	2.2 kW -230V 1-PH 50Hz (NK30P.3)
Radial Press force	135 Tons
Opening with dies	Ø Die + 28mm
	(Press path : +12mm)
Opening without dies	98mm
Length of Master Die shoes	75mm
Die sizes available	Ø6,8,10,12, <b>15*,18*,21*,24*,27*,</b> 30, <b>33*,39*</b> ,45, <b>48*</b> ,51,57
	* size included in standard Die Pack - 8 sets NK30
Dimension of the machine	Width : 800mm x Depth : 440mm x Height : 670mm
Options available	Quick Change Tool (QCT-NLS)
	<ul> <li>Individual Die Storage Rack (PDR-1)</li> </ul>
	Die Storage Panel (WP-12PDR)
	• Foot Switch (FS)
Net Weight	70 kgs (with oil, w/o dies)
Transport Packing details	Each machine on wood crate (NIMP15 conform)
	Packing dimensions : 58x70x75cms, 105 kgs (with 8 sets of dies)